

- ☐ SO. CALIFORNIA: 2044 South Vineyard Avenue, Ontario, CA 91761 • (909) 930-1822 • FAX (909) 923-2356
☐ NO. CALIFORNIA: 800 East Grant Line Road, Tracy, CA 95376 • (209) 830-8600 • FAX (209) 830-8884

City of Stockton
1465 S Lincoln Street
Stockton, CA 95206

December 7, 2023
Quote Number- 100878R2



Attention- Alanna Bindi
Reference- Link-Belt HTC 86110

City of Stockton Sourcewell ID: 26357
Link-Belt Sourcewell ID: 011723-LIN

Dear Alanna Bindi,

We are pleased to quote you One Link-Belt HTC 86110 equipped as follows:

Standard Unit:

BASE MACHINE DESCRIPTION (BASE ITEM)

BASE MACHINE F.O.B. LEXINGTON, KENTUCKY

Entire machine is pre-painted, and oven baked with a high solids paint (2 part epoxy primer/2 part polyurethane top coat).

CARRIER STRUCTURES

CHASSIS

8x4x4 drive/steering, 8 ft - 6 in. (2.59 m) wide, all welded box frame design, daytime running lights and complete travel light package with back-up alarm, right side and back-up viewing cameras, full deck aluminum fenders with mud flaps, lifting and tie down locations, and front and rear towing shackles.

OUTRIGGERS

Four dual stage beams with Confined Area Lifting Capacities CALC provide selectable outrigger extensions of full, intermediate and retracted. Hydraulically controlled from the operator's cab and on both sides of chassis with integral check valves and quick release "stow 'n go" 23.5" x 27.25" (59.7 cm x 69.2 cm) hexagonal steel pontoons. A fifth front bumper outrigger is hydraulically controlled from the operator's cab and at the front bumper of carrier with integral check valve and self-stowing 14.75 inch (37.5 cm) diameter steel pontoon.

SUSPENSION

Front and rear Air-Ride bogie beam.

AXLES

Axles 1 and 2 are hydraulic assist rack and pinion steering. Axles 3 and 4 are driven during on/off-highway travel. The drive axles have an inter-axle differential lockout.

BRAKES

Air actuated anti-lock (ABS) drum brakes on all wheels with spring applied / air released parking brakes on axles 2, 3, and 4.

TIRES

Four (single) 445/65R22.5 radials front and eight (dual) 315/80R22.5 radials rear mounted on aluminum disc wheels.

ENGINE

Diesel, and 12 volt start / 12 volt charging. [Note: brand, displacement, horsepower, block heater, and emission compliance listed in base item description.]

TRANSMISSION

ZF automated transmission with 12 speeds forward and 2 speed reverse.

PUMPS AND HYDRAULICS

6 gear type pumps, 3 pumps have a air-actuated disconnect. O-ring face seal componentry throughout with oil cooler.

-
- SO. CALIFORNIA: 2044 South Vineyard Avenue, Ontario, CA 91761 • (909) 930-1822 • FAX (909) 923-2356
 - NO. CALIFORNIA: 800 East Grant Line Road, Tracy, CA 95376 • (209) 830-8600 • FAX (209) 830-8884

DRIVER'S CAB

Single occupancy, environmental cab of LFC-2000 construction process. Includes fully enclosed modular compartment sealed with acoustical fabric lining, tinted safety glass for full vision, roll down left side window for ventilation, right side window, front window wipers and washer, engine instrumentation panel, cruise control, six way adjustable air-ride seat, seat belt, fire extinguisher, rear view mirrors, tilt steering wheel, air conditioning, overhead console with AM/FM radio, and engine dependent warm-water heater with defroster.

GENERAL CARRIER ITEMS

Four storage compartments, boom dolly/trailer electrical and air provisions, amber strobe light, clearance flags, left and right side air hose connection ports, left and right side bubble levels and 95 gallon (359.6 L) fuel tank with fuel water separator.

REVOLVING UPPERSTRUCTURE**UPPER FRAME**

All welded high strength steel frame with precision-machined surfaces for all components.

MAIN WINCH

Model 2M two speed, power up / power down winch package includes independent hydraulic controlled / pilot operated axial piston motor with disable switch, planetary gear reduction unit, automatic controlled spring applied / hydraulic released multiple disc brake, viewing camera and electronic drum rotation indicator. Drum includes grooved laggings and are mounted on anti-friction bearings. Provisions for future addition of auxiliary winch provided.

WIRE ROPE

730 ft. (222.5 m) of 19 mm (0.75 in.) 37x7 non rotating (Type KC) rope.

SWING

Includes independent electro-hydraulic controlled / pilot operated fixed displacement motor, planetary gear reduction unit, spring applied hydraulic released 360 degree multi-plate park brake, audio swing alarm, right side viewing camera, two position positive house lock, and free swing mode.

COUNTERWEIGHT

16,000 lbs (7.2 mt) of total counterweight consisting of four, hydraulically removable counterweights with capacities for 0 lbs (0 mt), 4,000 lbs (1.8 mt), 8,000 lbs (3.6 mt), 12,000 lbs (5.4 mt), and 16,000 lbs (7.2 mt) counterweight configurations.

OPERATOR'S CAB

Single occupancy, 0° to 20° tilting, environmental cab of galvaneal steel construction. Includes fully enclosed modular compartment sealed with acoustical fabric lining, tinted safety glass for full vision, sliding operator's door, sliding right side and rear window, swing up roof window with wiper, front window wiper and washer, circulating fan, engine instrumentation panel, six way adjustable seat, seat belt, fire extinguisher, rear view mirror, Link-Belt Pulse operating system including rated capacity limiter (anti-two block with function kick-out) with internal light bar and boom extend mode controller, foot throttle, arm chair dual axis (joystick) electronic controllers, outrigger sight level bubble and hand held outrigger control, cabwalk, cab mounted work lights, air conditioning, AM/FM radio with Bluetooth, and diesel fired warm-water heater with defroster.

GENERAL UPPERSTRUCTURE ITEMS

Fine metering, left side folding guardrail, and four (4) high intensity work lights.

TELESCOPIC BOOM**BOOM**

38 to 164 ft (11.5 to 50.0 m) pin & latch six section boom with quick reeve head machinery and selectable extension modes, five nylon head sheaves, deflector pads, mechanical boom angle indicator, wind speed indicator, two (2) adjustable boom floodlights, one (1) remote controlled boom floodlight, aviation obstruction marking light and flag, and boom dolly connection.

BOOM HOIST SYSTEM

One double acting cylinder with holding valve. Boom float kit for use with boom dolly.

- SO. CALIFORNIA: 2044 South Vineyard Avenue, Ontario, CA 91761 • (909) 930-1822 • FAX (909) 923-2356
- NO. CALIFORNIA: 800 East Grant Line Road, Tracy, CA 95376 • (209) 830-8600 • FAX (209) 830-8884

WARRANTY

12 month UNLIMITED hours material and workmanship - "See Link-Belt website under Service, Warranty statements, for details"

Options Included in Pricing Below:

➤ ICRANE - iCraneTrax Lite - A free 24-month subscription to Link-Belts telematics network. The network delivers real-time and historical data from anywhere you have an internet connection, and there's no obligation to share your data with the dealer or the factory. Setup your secure account at www.icranetrax.com/lbce . Note: International data dependent on cellular service.	N/C
➤ PREFER - Link-Belt Preferred - A free comprehensive library of on-line manuals, schematics, and bulletins for new and older Link-Belt cranes. There are also calculators for ground bearing, and operating costs. Sign up and start taking advantage of this and more at www.linkbelt.com .	N/C
➤ 3DLIFT - 3D Lift Planning - Create, save, view, and print three dimensional lift plans from anywhere you have an internet connection. There are no special software downloads and this service is free to Link-Belt crane owners. Create your own user secure account at www.3dliftplan.com .	N/C
➤ 1320 - REAR AIR RIDE LIFT SYSTEM - A cylinder controlled from the ground control outrigger stations located on each side of the carrier raises the rear air-ride suspension for improved ground clearance.	\$3,920
➤ 1260 - FILTER KIT (EPA 2020) - Includes an extra set of air, fuel, DEF, and oil filters for the EPA 2020 on-highway engine.	\$940
➤ 1100B - 50 State emissions compliant Cummins X12 diesel on-highway engine. EPA 2022/CARB 2022 Compliant. (Note: REQUIRED FOR SALE IN CALIFORNIA, PENNSYLVANIA, AND NEW JERSEY) NET PRICE- NO DISC	\$1,550
➤ 1410A - SPARE TIRE AND ALUMINUM DISC WHEEL - 445/65R22.5 (Note: Not mounted to the crane)	\$4,950
➤ 1430 - TIRE INFLATION - Includes an air hose long enough to reach all of the tires, a quick disconnect, moisture block, pressure gauge, bleeder valve, and air chuck. Supplements the two (2) standard air hose connections.	\$620
➤ 2020D - 48,600 LBS (22.0mt) OF COUNTERWEIGHT - [32,600 lbs (10.7mt) in addition to standard counterweight]-may effect roadability	\$57,700
➤ 2200A - AUXILIARY WINCH - Model 2M two speed, power up / power down, piston motor with automatic brake, electronic drum rotation indicator, shutdown switch, grooved lagging, and 600 ft. (182.88 m) of 19 mm (0.75 in) diameter 37 x 7 non rotating (Type KC) wire rope.	\$39,740
➤ 2220A - HOIST DRUM FOLLOWER - MAIN AND AUXILIARY - Spring tensioned roller that applies pressure on the cable to maintain uniform wraps on the drum.	\$3,790
➤ 2250B - 1ST LAYER INDICATOR AND 3RD WRAP FUNCTION KICK-OUT - MAIN AND AUXILIARY - Visual and audible indicators in the operators cab warns when the wire rope is on the first/bottom layer and kick-outs when the wire rope is down to the last three wraps.	\$5,730

- SO. CALIFORNIA: 2044 South Vineyard Avenue, Ontario, CA 91761 • (909) 930-1822 • FAX (909) 923-2356
- NO. CALIFORNIA: 800 East Grant Line Road, Tracy, CA 95376 • (209) 830-8600 • FAX (209) 830-8884

➤ 2616 - RCL EXTERNAL LIGHT BAR - Mounts on the operators cab and informs the ground crew when lift capacities are less than 90% (green), 90 to 100% (yellow), and 100% plus (red).	\$1,060
➤ 2640B - AMBER STROBE LIGHT - One (1) LED light that produces a pulse flash pattern and mounts on a post behind the operators cab.	\$1,040
➤ 2740B - SINGLE AXIS ELECTRONIC CONTROLLERS - Four (4) single axis controllers instead of the standard two (2) dual axis joystick controllers.	N/C
➤ 3010 - AUXILIARY LIFTING SHEAVE [Required for base rating lift]	\$3,280
➤ 3510C - 10 ft TO 35 ft TO 58 ft (3.0m TO 10.67m TO 17.68m) MANUALLY OFFSETTABLE THREE PIECE [BI-FOLD] LATTICE FLY - features Link-Belt Power Pinning with assist tools and hand crank. 1/2-inch Square Drive Cordless Impact Wrench is available through the Parts department, Part # 3P 1744.	\$94,430
➤ 9000L - 10 TON (9.07 METRIC TON) SWIVEL HOOK AND BALL [Weight: 584 lbs (265kg)]	\$2,930
➤ 9000N 60-TON (54.43 METRIC TON) 3 SHEAVE QUICK REEVE HOOK BLOCK WITH SAFETY LATCH [Weight: 1,150 lbs (523kg)]	\$13,070

List Sales Price: \$1,640,950.00
 3% Price Increase: \$49,228.50
Sourcewell Discount : - \$365,078.56
 Sales Price with Discount: \$1,325,099.94
 Dealer Items: \$76,437.00
 10% CARB Regulation Delay Price Increase: \$175,387.16
 9.00% Sales Tax: \$141,923.17
Delivery Freight: \$6,500.00
Sales Price Total: \$1,725,347.27

The above price(s) are valid for 80 days.

10% CARB Regulation Delay Price Increase is an estimated amount due to current CARB diesel engine regulation. This amount is subject to increase or decrease dependent on the timeframe of a CARB approved diesel engine for the quoted crane.

Dealer items include: PDI/DMV Registration/Start Up Training/ Inbound Freight from Manufacture, Crane Certification, Crane Profile, Factory Inspection, 3/8" Impact Power Tool for Lattice Fly

Due to the current supply chain and rising inflation, pricing is subject to change prior to delivery.

Crane will be driven from Lexington, KY to Tracy, CA and counterweight will be delivered via heavy haul (2 loads)

Crane will be driven from Tracy, CA to Stockton, CA and counterweight will be delivered via heavy haul (2 loads)

Thank you for the opportunity to quote on your equipment needs. Should you have any further questions, please feel free to contact me.

Sincerely,
 NIXON-EGLI EQUIPMENT CO.

Sean Hines

Sean Hines (510) 318-2799
Municipal Area Manager