

JOB # 387

sheet A3

FLOORING TO STRINGER 3

(A3 /

IDEAS & DESIGNS MAY NOT BE DUPLICATED WITHOUT WRITTEN PERMISSION FROM GIL VILLALVAZO & G S V DRAFTING EVISION GSV FRAMING NOTES — (N)TILE OVER — (N)1/2" CEMENT BD. NOTES: SERVICE WEATHER HEAD ALL WOOD FRAMED CONSTRUCTION SHALL CONFORM TO CRC
 ALL LUMBER SHALL BE GRADE MARKED AND SHALL CONFORM TO CRC
 AND SHALL BEAR THE APA GRADE STAMP.
 ALL MUD SILLS AND ALL LUMBER IN CONTACT WITH CONCRETE AND MASONRY (E)3/4"-1" PLY WD. GSV Drafting OR WITHIN 6" OF GRADE SHALL BE FOUNDATION GRADE REDWOOD OR PRESSURE TREATED DOUGLAS FIR. SHALL BE BONDED TO THE SERVICE EQPT (E)2X6 JOIST@16*O.C. gsvdrafting@gmail.com (209) 943-2136 A. ALL VERTICAL FRAMING LUMBER SHALL BE STANDARD GRADE DOUGLAS OR HIM FIR U.N. P.T.

5. ALL HORIZONTAL FRAMING LUMBER SHALL BE DOUGLAS FIR OR LARCH NO.2 2. GROUNDED CONDUCTOR TERMINATIONS. EACH GROUNDED CONDUCTOR(WHITE WIRE) SHALL TERMINATE WITHIN (N)4X4 P.T. POST MIN. U.N. P.T.

6. ALL BLOCKING AND FURING SHALL BE DOUGLAS FIR NO.2 MIN. U.N. P.T. GL VILLALVAZO TOCKTON, CA 95206 8. ALL MEMBERS SHALL BE FRAMED, ANCHORED, TIED AND BRACED SO AS TO DEVELOP STRENGTH AND RIGIDITY. Il Village -(N)(2)3/8"¢ LAG BOLTS X 4.5" W/WASHERS (TOP VIEW) ALL 2X LUMBER & 4X & 6X LUMBER P.T.=PRESSURE TREATED LEDGE OF HOUSE POST TO FLOOR DET. (13) 3/4" = 1'-0" (RELOCATED) CONC. SLAB NOTES ELEC. MAIN DICONECT & 1. 4" CONCRETE SLAB (3.5" MIN.) RECONECT 2. CONCRETE SHALL OBTAIN A MIN. 28 DAY CURE STRENGTH TO EQUAL 2500 PSI. (N)4X4 P.T. POST (A3) METER SEPARATIONS (N.T.S.) ___2X4 P.T. BOT. RAIL ablaFIGURE 32A HANDRAIL MOUNTING EXAMPLES (E)2X6 RIM JOIST —(N)(2)3/8"¢ LAG BOL (E)FOOTING 1 MINIMUM CLEARANCE OF ELECTRICAL CABLE POST TO FRAME A3 (SAMPLE) CLEARANCE FOR SERVICE DROPS \mathbb{Z} STAGGER CUT LAYOUT-W/ 1/8" SPACING / MOUNTED TO GUARD MOUNTED TO WALL _2X12 STRINGER CARBONELL LORA ST. 1, CA 95202 TREAD & RISER SIZE LEROY R. C 322 E. FLO STOCKTON, APN: (2)#8 X 2.5" WOOD SCREW AT EA. R311.7.7.3 TYPE 2 SIDE VIEW A DIMENSION MEASURED IN THE DIRECTION OF TRAVEL NOT LESS THAN THE WIDTH DATE 3-15-23 WOOD -2x12 P.T. STRINGER FIGURE 32B HANDRAIL GRIP SIZE DRAWING ARRESVIATIONS SCALE AS NOTED METAL. (E)=EXISTING STAIRS LAYOUT (N)=NEW

(RT)=REPLACEMENT

.25" X 3" SCREW

CRC 311.7.8 TO WAI HANDRAIL LAYOUT

MIN. ONE SIDE


STAIRS & HANDRAIL LAYOUT 6


(A3)


HANDRAIL DETAIL

N.T.S

(A3)







GSV DRAFTI